



**DVR608RT
DVR616RT**

D1 / 960H DVR Series



The **inMotion** DVR600RT series D1/960H Real Time DVRs are offered with 8 or 16 analogue inputs, a selection of Hard Disk sizes and a range of features to fulfil the requirements of most CCTV installations, with audio available on each channel and the ability to support a range of different telemetry protocols. In addition, the DVR offers streaming video to a web browser, a range of mobile devices and for more complex management requirements, Central Management Software to support the remote viewing and configuration of multiple sites from one or more control centers.

Features

- 8 or 16 channel Video and Audio recording
- WD1, WHD1, WCIF, D1, HD1 and CIF recording
- H.264 Video compression
- ADPCM Audio compression
- Dual Stream
- Mobile Device support
- Supports up to 2 internal SATA HDDs
- Scheduled recording
- Motion and Alarm Triggered Recording
- Per Channel Configuration
- Pre-Alarm Recording
- On Screen Motion Detection Indicator
- GUI
- VGA, HDMI & Composite Video monitor outputs
- IR Remote Control
- USB mouse
- Option DVD Writer
- Browser Based

Model	8 Channel	16 Channel	
Video Input	8x BNC, NTSC or PAL	16x BNC, NTSC or PAL	
Audio Input / output	8x RCA in / 1x RCA out	8x RCA in / 1x RCA out	
Display output	1x CVBS BNC, 1x VGA , 1x HDMI	1x CVBS BNC, 1x VGA , 1x HDMI	
Display Resolution	720P, 1080P, 1024x768, 1280x1024, 1366x768		
Recording / Playback Resolution & Frame Rate	NTSC: 240fps@WD1 PAL: 200fps@WD1	NTSC: 480fps@WD1 PAL: 400fps@WD1	
Compression Format	Video: H.264, Audio: ADPCM		
Recordign Formats	WD1, WHD1, WCIF, D1, HD1, CIF		
Hard Disk Support	Up to 2TB, SATA Interface, HDD x1 and DVD x 1		
Recording Control	Manual, Scheduled, Alarm, Motion triggered		
Alarm I/O	8x N.O./N.C. input, 1x N.O. Relay output	16x N.O./N.C. input, 1x N.O. Relay output	
Network Interface	10/100Mbps, RJ45		
Network Protocols	DHCP/Static, PPoE, DDNS		
Internet Bandwidth	Configurable		
Network Ports	Administrator definable		
USB Ports	2		
Remote Access	Web Interface, CMS Multi-Site Software application, Mobile Device		
Mobile Device Support	Android,iPhone/iPad		
PTZ Control	RS485 - Pelco P/D		
User Control	Front Panel Buttons, Mouse, IR Remote		
Operating Temperature	-10°C~+40°C (14°F~104°F)		
Power supply	DC12V <5.0A (Mains PSU supplied)		
Dimensions (LxWxH)	405mm x 321mm x 64mm (15.95" x 12.63" x 2.51")		
Weight	3Kg		
PAL Order Codes	No HDD	inDVR608RTP	inDVR616RTP
	500GB	inDVR608RTP-500	inDVR616RTP-500
	1TB	inDVR608RTP-1TB	inDVR616RTP-1TB
	2TB	inDVR608RTP-2TB	inDVR616RTP-2TB
NTSC Order Codes	No HDD	inDVR608RTN	inDVR616RTN
	500GB	inDVR608RTN-500	inDVR616RTN-500
	1TB	inDVR608RTN-1TB	inDVR616RTN-1TB
	2TB	inDVR608RTN-2TB	inDVR616RTN-2TB

inMotion International reserve the right to amend specifications and design without prior notice